



BS200-C

Product Description:

Specification	BS200-C Fingerprint Time Attendance Terminal
Display	4 lines, 16 characters each line Graphic Display LCD
LED indicator/Buzzer	2 LED(Red/Green) / 1 Buzzer
Display Language	Standard: English
Greeting Voice	Upon Request: Multinational Language
Keypad & button	16 key numeric & Function keypad
Dimension	190 x 140 x 57 mm
Sensor	
Sensor Type / Resolution	Optical (500 dpi)
Sensing Area	18mm x 22 mm
Storage Capacity	
Fingerprint Templates	3,000
Transaction	120,000
RF reader	
ID Card: 125 KHZ	Optional
MIFARE: 13.56 MHz	Optional
HID	Optional
I-Class card	Optional
Communications	
RS-232/485	Yes
TCP/IP	Yes
USB Client	N/A
USB Host	Yes
GPRS	Optional
Time Attendance	
Schedule Bell	Yes
Work Code	Yes
Operation Environment	
Power Consumption	DC 5V, 2A
Temperature	0°C ~ 45°C
Humidity	20% ~ 80%
Verification	
1:1 (Time)	<0.5 sec
1:N (Time)	<2 sec
FAR	≤0.0001%
FRR	≤1%
Standards Compliance	CE, FCC
More Standard Function	
Short Message (SMS)	Record checking, Ring bell, 9 digits-code, Time event transfer
More Optional Function	
Web server, Printer, RIS,	Backup battery, Soap function